

MONOPACK

CARE AND MAINTENANCE OF TIMBER SPORTS FLOORS

PRELIMINARY:

Thank you for choosing MONOPACK Sports Floor Finish. You are now equipped with a Restored/New performance floor and in order for you to get the most out of it, we recommend that these guidelines be followed. Initially the surface has a high sheen, but as it settles down, and is subjected to games use, an even low sheen patina develops. This is normal, and provides an excellent playing surface with good grip and good visibility without reflected glare.

SLIP HAZARDS:

Slip hazards can occur on sealed timber floors when dust and body fats build up. Dust from internal unpainted brickwork and from external sources is a major problem. Occasional scrubbing is necessary to remove the body fat build up. Dust and dirt from external sources must be controlled by placement of appropriate matting in all doorways and accompanied by daily sweeping of the floor. Failure to prevent ingress of dust and dirt will also damage the floor surface. Equipment and chairs used on the floor should be fitted with rubber floor protectors.

DUST CONTROL MATTING:

Dust control matting is essential for all entrances. Nomad Plus is recommended. It should be taken outside daily and shaken to remove loose dirt and then vacuumed. At least once per week the matting should be hung vertically and washed with running water from a garden hose.

DAILY SWEEPING:

The entire floor area requires sweeping at least once per day. The most practical method is to use scissor mops fitted with clean acrylic fringes.

CLEANING THE FLOOR:

If the floor becomes heavily soiled it will be necessary to wash with a solution of one (1) part MONOPACK FLOOR CLEAN to one hundred (100) parts warm water. The damage to timber floors caused by water is well known and it is important to ensure a minimum amount of water be allowed to remain in contact with the floor. The recommended method is to use an automatic scrubber fitted with a vacuum/squeegee attachment, but damp mopping is acceptable if excess liquid is squeezed from the mop. Remove black scuff marks with MONOPACK Spray On-Wipe Off Cleaner. Do not use wax or emulsion polishes on MONOPACK sealed floors, as they alter the grip factor and make the surface unsuitable for the application of further maintenance coats of MONOPACK SFF.

ANNUAL MAINTENANCE:

To maintain the surface in optimum condition, apply an additional coat of MONOPACK SFF each year.